

Glancetron 70-CT

Change tray and monitor in one device



- Digital change tray with integrated 17.8 cm (7") LCD monitor
- Tremendously sharp picture quality
- Ideal as ad presentation medium during payment process
- Splash-proof and impact resistant housing
- Two variants available: with USB port, or with VGA and DVI ports

Specifications

		GT 70-CT	GT 70-CT USB
Display	Screen diagonal / type	17.8 cm (7") / Anti-glare surface treatment LCD	
	Aspect ratio	16:9	
	Resolution (max.)	800 x 480 pixels	
	Active area (HxW)	152.4 x 91.5 mm	
	Response time	11 ms	
	Colours	262.144	
	Contrast	400:1	
	Brightness	350 cd/m ²	
	Viewing angle (H/V)	70° / 60°	
	Video input	VGA, DVI	USB
General	Colour	Black	
	Dimensions (WxHxD)	210 mm x 52 mm x 140 mm	
	Weight	675 g	
	Power supply	DC 12V	-
	Power consumption	Operating: 5.3 W / Sleep: n/a / Standby: lower then 3W	
	Mounting options	VESA 75 mm	
	Control buttons	-	
	Audio	n/a	
	Certifications	CE, FCC	
	Drivers	-	
Options	n/a		
Delivery contents	Power supply, VGA wire, VESA counter-top mounting	USB wire, VESA counter-top mounting	
Environment	Operating temperature	0 °C to +40 °C	
	Storage temperature	-10 °C to +50 °C	
	Operating humidity	20 % to 80 % (nicht kondensierend)	
	Storage humidity	10 % to 90 % (nicht kondensierend)	



Your partner